

<pre>\completeCOMBINEDLIST [...,.*,....] * inherits: \setupcombinedlist OPT instances: content</pre>	strc-lst.mkvi
<pre>\completecontent [...,.*,....] * inherits: \setupcombinedlist OPT</pre>	strc-lst.mkvi
<pre>\completelist [...<sup>1</sup>] [...,.*<sup>2</sup>,....] 1 LIST OPT 2 inherits: \setuplist</pre>	strc-lst.mkvi
<pre>\currentlistentrydestinationattribute</pre>	strc-lst.mkvi
<pre>\currentlistentrylimitedtext {...} * TEXT</pre>	strc-lst.mkvi
<pre>\currentlistentrynumber</pre>	strc-lst.mkvi
<pre>\currentlistentrypagenumber</pre>	strc-lst.mkvi
<pre>\currentlistentryreferenceattribute {...} * number text pagenumber all</pre>	strc-lst.mkvi
<pre>\currentlistentrytitle</pre>	strc-lst.mkvi
<pre>\currentlistentrytitlerendered</pre>	strc-lst.mkvi
<pre>\currentlistsymbol</pre>	strc-lst.mkvi
<pre>\definecombinedlist [...<sup>1</sup>] [...,.*<sup>2</sup>,....] [...,.*<sup>3</sup>,....] 1 NAME OPT 2 LIST 3 inherits: \setupcombinedlist</pre>	strc-lst.mkvi
<pre>\definelist [...<sup>1</sup>] [...<sup>2</sup>] [...,.*<sup>3</sup>,....] 1 NAME OPT OPT 2 LIST 3 inherits: \setuplist</pre>	strc-lst.mkvi
<pre>\definelistalternative [...<sup>1</sup>] [...<sup>2</sup>] [...,.*<sup>3</sup>,....] 1 NAME OPT OPT 2 NAME 3 inherits: \setuplistalternative</pre>	strc-lst.mkvi
<pre>\definelistextra [...<sup>1</sup>] [...<sup>2</sup>] [...,.*<sup>3</sup>,....] 1 NAME OPT OPT 2 NAME 3 inherits: \setuplistextra</pre>	strc-lst.mkvi
<pre>\determinelistcharacteristics [...<sup>1</sup>,....] [...,.*<sup>2</sup>,....] 1 LIST OPT 2 inherits: \setuplist</pre>	strc-lst.mkvi
<pre>\doifselist {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} 1 LIST 2 TRUE 3 FALSE</pre>	strc-lst.mkvi

<pre>\doifelsestructurelisthasnumber {...} {...} 1 TRUE 2 FALSE</pre>	strc-lst.mkvi
<pre>\doifelsestructurelisthaspage {...} {...} 1 TRUE 2 FALSE</pre>	strc-lst.mkvi
<pre>\doiflistelse {...} {...} {...} 1 LIST 2 TRUE 3 FALSE</pre>	strc-lst.mkvi
<pre>\doifstructurelisthasnumberelse {...} {...} 1 TRUE 2 FALSE</pre>	strc-lst.mkvi
<pre>\doifstructurelisthaspageelse {...} {...} 1 TRUE 2 FALSE</pre>	strc-lst.mkvi
<pre>\listlength</pre>	strc-lst.mkvi
<pre>\placecombinedlist [...]<sup>1</sup> [...,<sup>2</sup>...]<sup>OPT</sup> 1 LIST 2 inherits: \setupcombinedlist</pre>	strc-lst.mkvi
<pre>\placeCOMBINEDLIST [...,<sup>*</sup>...]<sup>OPT</sup> * inherits: \setupcombinedlist<sup>OPT</sup> instances: content</pre>	strc-lst.mkvi
<pre>\placecontent [...,<sup>*</sup>...]<sup>OPT</sup> * inherits: \setupcombinedlist<sup>OPT</sup></pre>	strc-lst.mkvi
<pre>\placelist [...,<sup>1</sup>...]<sup>OPT</sup> [...,<sup>2</sup>...]<sup>OPT</sup> 1 LIST 2 inherits: \setuplist</pre>	strc-lst.mkvi
<pre>\placerawlist [...]<sup>1</sup> [...,<sup>2</sup>...]<sup>OPT</sup> 1 LIST 2 inherits: \setuplist</pre>	strc-lst.mkvi
<pre>\rawstructurelistuservariable {...} * KEY</pre>	strc-lst.mkvi
<pre>\setupcombinedlist [...]<sup>1</sup> [...,<sup>2</sup>...]<sup>OPT</sup> 1 LIST 2 criterium = <u>local</u> intro reference SECTIONBLOCK:reference all SECTIONBLOCK:all text SECTIONBLOCK:text current SECTIONBLOCK:current here previous SECTIONBLOCK:previous component SECTION SECTIONBLOCK:SECTION reference = NUMBER extras = NAME order = command all title alternative = a b c d e f g left right top bottom command none interactive paragraph horizontal vertical NAME</pre>	strc-lst.mkvi
<pre>\setupCOMBINEDLIST [...,<sup>*</sup>...]<sup>OPT</sup> * inherits: \setupcombinedlist instances: content</pre>	strc-lst.mkvi
<pre>\setupcontent [...,<sup>*</sup>...]<sup>OPT</sup> * inherits: \setupcombinedlist</pre>	strc-lst.mkvi

```
\setuplist [...,1...] [...,2...,...]
```

```
1 LIST OPT
2 state = start stop
location = none here
type = simple command userdata
criterium = local intro reference SECTIONBLOCK:reference all SECTIONBLOCK:all text SECTIONBLOCK:text
current SECTIONBLOCK:current here previous SECTIONBLOCK:previous component SECTION SECTIONBLOCK:SECTION

list = NAME
width = fit broad auto DIMENSION
height = fit broad DIMENSION
depth = fit broad DIMENSION
symbol = one two three none default
label = yes no none NAME
starter = COMMAND
stopper = COMMAND
command = \...##1##2##3
numbercommand = \...##1
textcommand = \...##1
pagecommand = \...##1
pagenumber = yes no always
headnumber = yes no always
before = COMMAND
after = COMMAND
inbetween = COMMAND
margin = none DIMENSION
distance = none DIMENSION
aligntitle = yes no
numeralalign = left right middle flushleft flushright inner outer
align = inherits: \setupalign
hang = yes no
left = COMMAND
right = COMMAND
interaction = yes no all number text title page sectionnumber pagenumber
limittext = yes no TEXT
style = STYLE COMMAND
color = COLOR
numberstyle = STYLE COMMAND
numbercolor = COLOR
textstyle = STYLE COMMAND
textcolor = COLOR
pagestyle = STYLE COMMAND
pagecolor = COLOR
reference = NUMBER
extras = NAME
order = command all title
alternative = a b c d e f g left right top bottom command none interactive paragraph horizontal vertical
NAME

maxwidth = DIMENSION
pageprefix = yes no
pageprefixseparatorset = NAME
pageprefixconversionset = NAME
pageprefixset = NAME
pageprefixsegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all SECTION SECTION:SECTION SECTION:* SECTION:all
pageprefixconnector = COMMAND PROCESSOR->COMMAND
pageconversionset = NAME
pagestarter = COMMAND PROCESSOR->COMMAND
pagestopper = COMMAND PROCESSOR->COMMAND
inherits: \setupcounterinherits: \setupframed
```

strc-lst.mkvi

```
\setuplistalternative [...,1...] [...,2...,...]
```

```
1 NAME OPT
2 before = COMMAND
after = COMMAND
command = \...##1##2##3
renderingsetup = NAME
width = DIMENSION
distance = DIMENSION
stretch = DIMENSION
filler = COMMAND
```

strc-lst.mkvi

```
\setuplistextra [...,1...] [...,2...,...]
```

```
1 NAME OPT
2 before = COMMAND
after = COMMAND
```

strc-lst.mkvi

\startcurrentlistentrywrapper ... \stopcurrentlistentrywrapper	strc-lst.mkvi
\structurelistuservariable {...} * KEY	strc-lst.mkvi
\writebetweenlist [ <sup>1</sup> ...] [ <sup>2</sup> ... <sub>OPT</sub> ...] {... <sup>3</sup> } 1 LIST 2 inherits: \setuplist 3 COMMAND	strc-lst.mkvi
\writedatatolist [ <sup>1</sup> ...] [ <sup>2</sup> ... <sub>OPT</sub> ...] [ <sup>3</sup> ... <sub>OPT</sub> ...] 1 LIST 2 inherits: \setuplist 3 KEY = VALUE	strc-lst.mkvi
\writetolist [ <sup>1</sup> ...] [ <sup>2</sup> ... <sub>OPT</sub> ...] {... <sup>3</sup> } {... <sup>4</sup> } 1 LIST 2 inherits: \setuplist 3 NUMBER 4 TEXT	strc-lst.mkvi