



Main

Link Setup


Network

Advanced

Services

System

PicoSta

Base Station SSID:	<input type="text" value="KYWIFI-37"/>	AP MAC:	<input type="text" value="00:0E:2E:AF:47:32"/>
Signal Strength:	 -65 dBm		
TX Rate:	<input type="text" value="5.5 Mbps"/>	RX Rate:	<input type="text" value="11 Mbps"/>
Frequency:	<input type="text" value="2462 MHz"/>	Channel:	<input type="text" value="11"/>
Antenna:	<input type="text" value="Main"/>	Noise Floor:	<input type="text" value="-88 dBm"/>
Security:	<input type="text" value="none"/>	ACK Timeout:	<input type="text" value="33"/>
Transmit CCQ:	<input type="text" value="48%"/>	QoS Status:	<input type="text" value="Auto Priority"/>
Uptime:	<input type="text" value="01:11:20"/>	Date:	<input type="text" value="2009-12-18 17:14:31"/>
LAN Cable:	<input type="text" value="ON"/>	Host Name:	<input type="text" value="Isaac"/>
LAN MAC:	<input type="text" value="00:15:6D:AC:E5:CD"/>	LAN IP Address:	<input type="text" value="192.168.100.1"/>
WLAN MAC:	<input type="text" value="00:15:6D:AB:E5:CD"/>	WLAN IP Address:	<input type="text" value="10.10.7.104"/>
Extra info:	<input type="text" value="----"/>	Tools:	<input type="text" value="----"/>

Refresh

**LAN STATISTICS**

	Bytes	Packets	Errors
Received:	<input type="text" value="5065650"/>	<input type="text" value="21155"/>	<input type="text" value="0"/>
Transmitted:	<input type="text" value="39719304"/>	<input type="text" value="31468"/>	<input type="text" value="0"/>

**WLAN STATISTICS**

	Bytes	Packets	Errors
Received:	<input type="text" value="33775334"/>	<input type="text" value="26794"/>	<input type="text" value="0"/>
Transmitted:	<input type="text" value="2636680"/>	<input type="text" value="15448"/>	<input type="text" value="0"/>

**WLAN ERRORS**

Rx Invalid NWID:	<input type="text" value="0"/>	Tx Excessive Retries:	<input type="text" value="0"/>
Rx Invalid Crypt:	<input type="text" value="0"/>	Missed Beacons:	<input type="text" value="0"/>
Rx Invalid Frag:	<input type="text" value="0"/>	Other errors:	<input type="text" value="0"/>

Refresh